

ORIGINAL EQUIPMENT WARRANTY POLICIES

CONSUMER LIMITED WARRANTY FOR ORIGINAL EQUIPMENT PASSENGER & LIGHT TRUCK TIRES INCLUDING TEMPORARY TIRES

I. WHAT IS COVERED AND FOR HOW LONG

Kumho warrants that a tire manufactured by Kumho and/or equipped originally on the vehicle is free from defects in materials and/or workmanship in normal use for the life of the original usable tread. The life of the original usable tread ends when the tire tread has been worn down with only 2/32" (1.6 mm) remaining, at which point the tire is considered to be fully worn out.

PASSENGER AND LIGHT TRUCK TIRES

A. Free replacement

If a Kumho Radial Passenger or Light Truck tire fails as a result of defect in materials and/or workmanship within the first 2/32" of the original tread depth, the tire will be replaced with a new, comparable Kumho tire at no charge including mounting and balancing charges.

B. Pro-rata replacement

A tire not qualifying for free replacement will be given a credit toward the purchase of a new, comparable Kumho tire based upon the amount of tread actually worn. The cost of mounting, balancing and any other service charges or applicable taxes should be paid by the user. Otherwise adjustment for compensation will be made on a pro-rata basis calculated by multiplying the actual current dealer selling price by the percentage of remaining usable tread depth.

KUMHO TEMPORARY TIRE

- A. A Temporary Tire weighs less and provides more trunk storage space than a conventional tire. To conserve tire tread life, the temporary tire should be returned to the trunk as soon as it is convenient to have your standard tire repaired or replaced.
- B. If a Kumho Temporary Tire fails as a result of defect in materials and/or workmanship during the first 50% of usable tread wear, the tire will be replaced with a new, comparable tire at no charge including mounting and balancing charges. No adjustment will be made for tires that are worn more than 50%.

II. WHAT IS NOT COVERED BY THE WARRANTY

NON-ADJUSTABLE CONDITIONS

- A. Irregular wear or tire damage due to:
 - 1. Road hazards such as punctures, cuts, snags, scuffs, carcass bruised or impact breaks.

- 2. Fire, wreck, vandalism or collision.
- 3. Improper inflation, overloading, high-speed spinning, improper mounting or demounting, running flat, off-road use, racing, vandalism, willful damage or abuse.
- 4. Misalignment, wheel imbalance, defective brakes or shock absorbers, or use of tire chains.
- 5. Any tire which has failed as a result of adding material (e.g., tire fillers, sealant, or balancing substances).

- B. Tire fitted to anything other than the original vehicle.
- C. Tire worn beyond tread wear indicator (2/32" or 1.6 mm tread remaining).
- D. Tire presented by other than the actual owner-user.
- E. Tire branded "NA" (meaning non-adjustable) or "blem" (meaning blemished).
- F. Loss of time inconvenience, loss of use of the vehicle or consequential damage.
- G. Ride disturbance after free-replacement conditions.
- H. Ozone or weather cracking on tires over four (4) years from the date of manufacture.
- I. No flat spot warranty for original tires.
- J. No mileage warranty for original tires.
- K. This limited warranty applies only to the original vehicle owner and is non-transferable.

GENERAL EXCLUSIONS

- A. No Kumho Tire employee, retailer or dealer has the authority to make any warranty, representation, promise or agreement on behalf of Kumho Tire except as stated in this policy.
- B. Tires used in racing-related activities or competitive events are not covered by this warranty.
- C. Limitation of remedy: To the extent permitted by law, Kumho disclaims liability for all consequential and incidental damages. Some provinces and states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have rights which vary from province to province in Canada, and from state to state in the United States.

ORIGINAL EQUIPMENT WARRANTY POLICIES

III. KUMHO OBLIGATIONS

Replacement tires qualifying under this warranty will be made by a participating Kumho dealer or a participating car dealer.

IV. OWNER'S OBLIGATIONS

- A. Conform to all pertaining policies detailed herein.
- B. Present tire to any authorized Kumho dealer or a participating car dealer along with proof indicating you are the original vehicle owner. Respective dealer will inspect tire in order to identify whether or not it qualifies for warranty based on the policies detailed herein.
- C. To locate an authorized Kumho dealer, use our web address kumhotire.ca/en/dealer/list or call (877) HI-KUMHO.

WARNING FOR YOUR SAFETY

• TIRE DEMOUNTING AND MOUNTING

Improper tire mounting and inflation procedures may cause tire beads to break with explosive force during installation of the tire on the rim, causing personal injury and property damage. Follow the Rubber Manufacturers Association (RMA) installation and safety procedure for mounting and inflating tires. Tire and rim must match in size. Rim parts must match in size. Rim parts must match by manufacturer's design. Clean rim. Lubricate rim and beads. Do not exceed the maximum recommended pressure to seat beads on rim. Use remote control inflation equipment and inflation cage.

Note: Never inflate over 40 psi to seat beads. Mount radial-ply tires only on rims designated by wheel manufacturer as suitable for radial tires. Only specially trained persons shall mount tires.

• AIR PRESSURE

Check the pressure in your tires, including your spare, at least monthly, and always before and during extended driving, when tires are cold (at least 3 hours after the vehicle has been stopped and before it is driven more than 1 mile/1.6 km). Do not reduce pressure when tires are hot: use an accurate air pressure gauge to check pressure and maintain it at the level recommended on the vehicle tire placard or in the owner's manual. Underinflation produces extreme flexing of sidewalls and builds up heat to the point that premature tire failure may occur. Overinflation can cause the tires to be more susceptible to impact damage. Cold tire pressures, however, should never be higher than the limit molded on the sidewall.

• LOAD LIMITS

Never exceed the load-carrying limits molded onto the sidewall of your tires or the maximum vehicle load limit as shown on the vehicle tire placard, whichever is less. Overloading builds up excessive heat in the tire and leads to early and/or sudden failure.

• HAZARDS

Avoid running over objects (e.g., chuckholes, rocks, curbs, metal, glass, etc.) which may possibly cause internal tire damage. Continued use of a tire that has suffered internal damage, which may not be externally visible, can lead to dangerous tire failure. Determination of suspected internal damage requires demounting the tire from its rim and examination by trained personnel.

• WORN TIRES

Never drive on worn tires. Tires should be replaced by trained personnel when 2/32" (1.6 mm) of remaining tread depth, as indicated by tread wear indicators molded into the tread grooves. Use of worn-out tires (less than 2/32" remaining tread depth) increases the possibility of tire failure. In most states, it is illegal to drive with less than 2/32" of remaining tread depth.

• SPEED LIMITS

Operating your vehicle in excess of lawful speed limits or the maximum speeds justified by driving conditions can be dangerous. Excessive speed creates heat buildup in a tire, leading to possible tire failure.

• SPEED-RATED TIRES

Speed-rated tires are identified by letters P, Q, S, T, H, V, W or Z as either part of the size designation (e.g., HR) or part of the service description adjacent to the size designation (e.g., 94H) and indicate the maximum speed capability of the tire when properly loaded and inflated. However, even when properly loaded and inflated, driving for prolonged periods at high speeds can cause tire damage and possible tire failure which could lead to an accident. Original equipment speed-rated tires must be replaced with tires of the same or higher speed rating if the speed capability of the vehicle is to be maintained. Consult your Kumho dealer for the tires best suited to your vehicle driving habits. Repair of speed-rated tires must be done in accordance with RMA repair procedures and is limited to one 1/3" diameter repair in the tread area.

• TIRE ROTATION

Rotate your tires for longer tire life. Front and rear tires perform different jobs and wear differently. Consult your vehicle owner's manual for mileage recommendations and rotation patterns.

ORIGINAL EQUIPMENT WARRANTY POLICIES

- **ADDITIONAL SAFETY INFORMATION FOR TEMPORARY TIRE**

- A. **Air pressure**

- Check inflation pressure as soon as possible after installation and inflate to 60 psi. The tire pressure should be checked monthly and maintained at 60 psi while the tire is stored or in service.

- B. **Vehicle restriction**

- The temporary spare tire was specifically designed for your car and should not be used on any other vehicle.

- C. **Other restrictions**

- The temporary spare tire should not be used with other wheels, nor should standard tires, snow tires, wheel covers, or trim rings be used with the temporary spare wheel. If such use is attempted, damage to these items or other vehicle components may occur.

WARRANTY POLICIES

Adjustment Credit Percentage Percentage Kumho Tire pays based on remaining tread depth

RTD (Remaining Tread Depth)*	OTD (Original Tread Depth)*																								
	8/32	9/32	10/32	11/32	12/32	13/32	14/32	15/32	16/32	17/32	18/32	19/32	20/32	21/32	22/32	23/32	24/32	25/32	26/32	27/32	28/32	29/32	30/32	31/32	32/32
2/32	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
3/32	35	14	13	11	10	9	8	8	7	7	6	6	6	5	5	5	5	4	4	4	4	4	4	3	3
4/32	50	29	25	22	20	18	17	15	14	13	13	12	11	11	10	10	9	9	8	8	8	7	7	7	7
5/32	63	43	38	33	30	27	25	23	21	20	19	18	17	16	15	14	14	13	13	12	12	11	11	10	10
6/32	75	57	50	44	40	36	33	31	29	27	25	24	22	21	20	19	18	17	17	16	15	15	14	14	13
7/32	100	100	63	56	50	45	42	38	36	33	31	29	28	26	25	24	23	22	21	20	19	19	18	17	17
8/32	100	100	100	67	60	55	50	46	43	47	38	35	33	32	30	29	27	26	25	24	23	22	21	21	20
9/32		100	100	100	70	64	58	54	50	48	44	41	39	37	35	33	32	30	29	28	27	26	25	24	23
10/32			100	100	100	73	67	62	58	53	50	47	44	42	40	38	36	35	33	32	31	30	29	28	27
11/32				100	100	100	75	69	64	60	56	53	50	47	45	43	41	39	38	36	35	33	32	31	30
12/32					100	100	100	77	71	67	63	59	56	53	50	48	45	43	42	40	38	37	36	34	33
13/32						100	100	100	79	73	69	65	61	58	55	52	50	48	46	44	42	41	39	38	37
14/32							100	100	100	80	75	71	67	63	60	57	55	52	50	48	46	44	43	41	40
15/32								100	100	100	81	76	72	68	65	61	59	57	54	52	50	48	46	45	43
16/32									100	100	100	82	78	74	70	67	64	61	58	56	54	52	50	48	47
17/32										100	100	100	83	79	75	71	68	65	63	60	58	56	54	52	50
18/32											100	100	100	84	80	76	73	70	67	64	62	59	57	55	53
19/32												100	100	100	85	81	77	74	71	68	65	63	61	59	57
20/32													100	100	100	86	82	78	75	72	69	67	64	62	60
21/32														100	100	100	86	83	79	76	73	70	68	66	63
22/32															100	100	100	87	83	80	77	74	71	69	67
23/32																100	100	100	88	84	81	78	75	71	70
24/32																	100	100	100	87	85	81	79	76	73
25/32																		100	100	100	88	85	82	79	77
26/32																			100	100	100	89	86	83	80
27/32																				100	100	100	89	86	83
28/32																					100	100	100	90	87
29/32																						100	100	100	90
30/32																							100	100	100
31/32																								100	100
32/32																									100

*Measurements are in inches.